

Spider Lifter – PNT4RP (4 Suction Pads in Crossed Position) for Doors or Windows

PNEUMATIC VACUUM LIFTER FOR DOORS AND WINDOWS

Features:

- Four suction pads.
- High-limit yielding steel suction pads made of first quality materials.
- Standard gaskets made from rubberized fabric, suitable for surfaces with small irregularities.
- Fixed central beam with 2 cross-positioned tubes with longitudinal adjustment.
- Longitudinal and transversal adjustment.
- Steel Counter plate complete with diamond point rubber.
- Larger vacuum tube.
- High-limit yielding steel frame.
- Structure with 0-90° pneumatic tilting.
- Continuous vacuum pump powered by compressed air.
- Silencers.
- Vacuum gauge with graduated and coloured scale to monitor the degree of vacuum.
- Powered by a powerful and quiet vacuum generator.
- Air consumption 6/7 Bar.
- Operating pressure 500 l/min.
- Acoustic and visual alarm system which automatically signals a low vacuum degree. The alarm system works autonomously by means of rechargeable batteries and it is supplied with the appropriate battery charger.
- Manoeuvring handle for the operator with the gripping and release commands.
- Central suspension hook.

Specifications:

Lift capacity: 90Kg

Suction Pads: x4

Suction pads dimensions: 400mm x 90mm

Tilt facility: 0-90 degrees pneumatic tilting

