

EHL Highlifter – benefits and features

High efficiency = high performance

- The working height can be adjusted
- * Opportunities for optional extras (remote control, level control etc.)
- Great manoeuvrability
- * Forks stop quickly and precisely
- * Capacity 1,500 kg to lifting height 400 mm
- * Low own weight

High safety

- * Central location of control buttons
- * Emergency stop centrally placed
- * Low overall height
- Supporting stabilisers at steering wheels
- * Tandem wheels on scissors legs
- * Low noise level (fine tolerances and rubber softened wheel holder)
- 1200 mm forks ensure optimum support for the pallet
- * Brake at fork wheel

Optimum ergonomics

- * Ergonomically correct handle
- Lift height adjustable to individual requirements (reduces strain on back and shoulders)
- * Rounded corners meaning less damage to surroundings

Great durability = low costs

- Long operating life
- * Low maintenance costs (simple construction, easy to replace parts)
- * Reliable cylinder construction (patented with twin seals)
- Strong construction
- * Use of quality materials
- Low current consumption – permanent magnet motor
- * Maintenance-free motor
- * Pump unit with special oil for long durability

High flexibility

- * Many different fork lengths and width
- * Tailor-made solutions
- * Available in stainless plus and semi stainless versions
- * Available in explosion proof version
- * Available in antistatic version
- Different wheel materials available
- * Different batteries and chargers



*Features marked with * are unique for the Logitrans products*