

## LOGIFLEX SELF MAXI - benefits and features

### Great durability = low costs

- Quality everywhere (choice of material, tolerances, construction) – minimum wear
- Simple construction = easy to exchange wearing parts
- Low power consumption = long battery life time
- \* AC technology
- \* No brushes in drive motor
- \* Constant pressure on drive wheel = minimum wear
- \* Pump unit with special oil = great durability
- \* Easy access to battery for maintenance
- \* Adjustable carriage rollers
- \* Battery can be moved sideways = to facilitate easy maintenance
- Service manual available on the internet

### Lifting performance = user-friendly and efficient

- \* Ergonomic handle
- \* Multiflex function = easy operation
- \* Close tolerances = low noise level
- \* Remote control and level control with safety stop
- \* Continuous product development = lifting performance for the customer
- \* Part free lift telescopic mast
- \* Low own weight = low current consumption = long operating
- \* Short overall measurements = small space requirements
- \* Hour counter and battery indicator
- Small turning angle
- Adjustable acceleration and speed
- Infinitely variable speed control
- \* Width 635 mm to lifting height 2450

### Optimum safety

- \* Safety stop both horizontally and vertically on the tiller arm
- Reduced speed at lifting heights above 400 mm
- All control buttons on handle
- Foot protectors
- Shielded chains
- \* Instant stop (forks stop quickly and precisely)
- \* Lowering valve directly on cylinder = safety in case of hose breaches
- Fulfils all CE requirements
- \* Motor brake

### High flexibility

- \* Many different fork & leg lengths and types = individual customer requirements
- \* Adjustable carriage for optional extras = solves many application situations
- \* Large range of optional extras
- \* Possible to adapt to individual customer requirements
- \* Explosion proof version available
- \* Possible to choose individual colours
- \* Built-in or external charger
- \* Also available with adjustable fork span



Features marked with \* are unique for the Logitrans products